



## SLIMLINE SERIES

The Slimline Floodlight range, with optional integrated sensor, is lightweight and easy to install. Using Phillips LED chips and delivering 120+ lumens per watt, this highly efficient floodlight combines high energy savings and crisp, even light distribution across its broad beam angle.

With an IP65 rating and suitability across a wide temperature range, the Slimline Floodlight is built to withstand the elements.

## FEATURES

- Optional integrated motion and daylight sensor (with on/off switch)
- Light weight slimline
- High efficacy
- Flex and plug included
- IP65 rating
- IES files available on request

## CHARACTERISTICS

POWER FACTOR	>0.9	MODEL NUMBER	CCT	DIMENSIONS	WATT	LCP	LUMENS	EFFICACY
CRI	>80	EP-FL-15	5000K	148x38x117mm	15W	14.04W	1,800	120lm/W
BEAM ANGLE	110°	EP-FL-30	5000K	200x43x149mm	30W	30.33W	3,600	120lm/W
IP RATING	65	EP-FL-50	5000K	250x51x188mm	50W	50.96W	6,000	120lm/W
LIFETIME (L <sub>70</sub> )	>60,000h							
WARRANTY	5 Years							



[sales@emeraldplanet.com.au](mailto:sales@emeraldplanet.com.au)

[www.emeraldplanet.com.au](http://www.emeraldplanet.com.au)

