



TORRENT SERIES

Designed for performance, reliability and the ability to manage the harsh weather conditions of Australia, the Torrent Floodlight is a perfect option for commercial applications. Its high efficacy of 130+ lumens per watt delivers optimum performance, complemented by its diffuse lens and adjustable bracket which enables easy installation across a range of applications.

With an IP65 rating and tolerance across a wide ambient temperature range, the Torrent Series is built to last.

FEATURES

- High efficacy
- IP65 rating
- Adjustable bracket for easy installation
- Flex and plug included
- IES files available on request

ACCESSORIES

- Glare guard
- Protective wire mesh guard

CHARACTERISTICS

POWER FACTOR	>0.9	MODEL NUMBER	CCT	DIMENSIONS	WATT	LCP	LUMENS	EFFICACY
CRI	>80	EP-FL-70	5000K	260x275x102mm	70W	69.81W	9,100	130lm/W
BEAM ANGLE	110°	EP-FL-100	5000K	260x275x102mm	100W	99.32W	13,000	130lm/W
IP RATING	65	EP-FL-150	5000K	296x316x102mm	150W	149W	19,500	130lm/W
LIFETIME (L ₇₀)	>60,000h							
WARRANTY	5 Years							

VEET Approved VIC	ESS Approved NSW	EEIS Approved ACT	REES Approved SA	SAA	NATA	RCM
-------------------------	------------------------	-------------------------	------------------------	-----	------	-----

sales@emeraldplanet.com.au

www.emeraldplanet.com.au

